

300W PRODUCT SPECIFICATION SHEET



Product Specifications		配件: Accessories			
Built-in Battery	High Quality Lithium ion Batteries 296Wh, 20Ah/14.8V (8000mAh/3.7V)				
Input Charging/Fully Charged Time	Adapter: DC19V/3A /DC:7~8 (DC5521) Power adapter: DC19V/3A (DC5521)/DC:7h~8h				
Solar Panel Input	MPPT, 18V~22V/3.0A MPPT, 18V~22V/3.0A Max				
USB Output	USB1: 5V/1A USB2: 5V/2A USB3输出: 5V/3A USB1 output: 5V/1A USB2 output: 5V/2A USB3 output: 5V/3A 2 x USB 输出 5~12V/18W(QC3.0) 2 x USB output 5~12V/18W(QC3.0) 1 x Type-C 输出 PD18W 1 x Type-C output PD18W 1 x Type-C 输出 PD27W 1 x Type-C output PD27W				
DC Output	2 x 12~16.5V/10A(13.5A Max) DC output 2 x 12~16.5V/10A(13.5A Max) (DC5521)	Number of containers			
AC Output	AC SineWave Output 110V/220V/230V±5V, 60Hz/50Hz±3Hz	20 'cabinet	40 'cabinet	45 foot high cabinet	45 foot high cabinet
		20 'open top cabinet	40 'open top cabinet	20 'flat bottom cabinet	40 'flat bottom cabinet
AC Continuous Output	300W	1134	2394	1134	1710
AC Max Output	500W about 1s	T300 Packing			
Bulb Type	4W LED Long bright, SOS, burst flash7		UNIT	GIFT BOX	EXP CARTON
Operation temperature	-10℃-40℃	Length (mm)	220	334	610
Lifecycle	>500 times	Width (MM)	145	194	355
Certification	CE, FCC, RoHS, PSE, MSDS, UN38.3,	Height (MM)	188	245	290
		Weight (KG)	2.85	3.9	12.5
		Units per Export Carton	3		
MultiSafety Protections	a.Short-circuit protection b.Over-current protection c.Over-voltage protection d.Low-voltage protection e.Over-load Protection f.Over-temperature protection	Packing list			
		1 x Portable power supply 1 x power adapter 1 x Cigarette Lighter 1 x User Manual			